



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 11/06, 15/00	A1	(11) International Publication Number: WO 00/01434 (43) International Publication Date: 13 January 2000 (13.01.00)
(21) International Application Number: PCT/GB98/01994 (22) International Filing Date: 7 July 1998 (07.07.98) (71) Applicant (for all designated States except US): THE UNIVERSITY OF SHEFFIELD [GB/GB]; Western Bank, Sheffield S10 2TN (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): HIGENBOTTAM, Timothy, William [GB/GB]; The Barn, Storrs Lane, Storrs, Sheffield S6 6GY (GB). HELLER, Benjamin, Wolf [GB/GB]; 47 Freedom Road, Walkley, Sheffield S6 2XA (GB). McCORMACK, Keith, Muir [GB/GB]; 1 Ranelagh Drive, Sheffield S11 9HE (GB). (74) Agent: HOOPER, John, Peter, Lindesay; 5 Haslingfield Road, Harlton, Cambridge CB3 7ER (GB).		(81) Designated States: AU, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: INHALERS <div style="text-align: center;"> </div> (57) Abstract <p>The present invention proposes treatment apparatus – specifically and in particular small (pocket-sized) hand-held apparatus. It suggests apparatus for the delivery of a medicament into the Patient's lungs in the form of a bolus, pulse, or spike of the medicament entrained in and driven by the normal respiration air, which apparatus comprises a drug dispenser (that in essence may be a conventional nebuliser or a dry-powder delivery system (11), in the reservoir (12) of which is stored the medicament to be administered, driven by some suitable pressurized gas from a valved cylinder (18) thereof to deliver an aerosol cloud of medicament into a tube (103) through which the Patient is breathing (by mouth) normal air, the gas cylinder valve (19) being controlled by a suitable programmed computing device (101) that is fed data describing the pressure within the breathing tube (103) and so is able to open and close the valve (19) at and for a time such as to drive the dispenser (11) to deliver (to the tube and thence to the Patient's lungs) a required pulse of medicament at any selected point within the Patient's respiratory cycle.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Inhalers

This invention relates to inhalers, and concerns in particular medical inhaler apparatus for use in the treatment of certain lung diseases or conditions.

In the Specification of British Patent Application No: 2,283,179 (which corresponds to published PCT International Application WO 95/10,315) there is described and claimed a novel method, and associated apparatus, for the use of nitric oxide in the treatment of various lung conditions and diseases. The present invention relates to improved apparatus which can be used not only for this purpose but also in the treatment of other lung problems.

There are many lung diseases and conditions - suffered both by humans and by other animals - for which the preferred form of treatment involves delivering a medicament of the appropriate sort down the Patient's airways into the lungs themselves, where the medicament can act upon, and perhaps be absorbed into, the tissues of the lungs. One such condition is asthma (an increasingly prevalent and worrying problem), in which the peripheral parts of the lung, namely those tiny airways and air spaces known respectively as bronchioles and alveoli, constrict to restrict the flow of air therethrough.

In other lung conditions the lung's small peripheral arteries - the pulmonary arteries - also constrict, typically those deep in the lungs where the oxygen tension falls as in an asthmatic attack, pneumonia, or chronic lung diseases like bronchitis and emphysema (and it should also be noted that such constriction often occurs without the causative

mechanism being fully explained; this is the so-called primary pulmonary hypertension).

The most effective treatments for asthma and like conditions involve the inhalation as an aerosol of some suitable chemical agent in normally inhaled air. At present, to deal with the problem of constricted small pulmonary arteries only a few relieving substances are known, and one of the most powerful - that known as *prostacyclin*, an extremely potent vasodilator - has to be administered on a continuous basis by infusion into a vein and so to the pulmonary arteries.

The aforementioned British and International Specifications relate to the use of nitric oxide (NO), another well-known and effective dilating agent for treating both lung problems of the blood-vessel-constriction type and of the asthma airway type. More specifically, these Specifications concern the manner in which nitric oxide is administered, and the apparatus used for this administration; they propose that the nitric oxide be administered to the Patient not continuously (either in admixture with, or separately but side by side with a supply of, air, oxygen or oxygen-enriched air) but intermittently and in short pulses of known, pre-determined volume at one or more suitable time during each inhalation. In the treatment of the constriction of the small pulmonary arteries the very short pulse, or spike, of nitric oxide is provided at the start of the inhalation, such that the resultant bolus of nitric oxide mixture inhaled by the Patient has a nitric oxide concentration high enough to have the desired therapeutic effect, even if admixed with some additional air, but is of such short duration (both in time and, as a result, in physical length) that, pushed by the following much larger volume of plain, and

therefore nitric oxide-free, air/oxygen, it reaches deeper into the lungs, where it both acts on the small pulmonary arteries and is taken up into the capillaries to react with haemoglobin (so preventing the formation of nitrogen dioxide). By contrast, in the treatment of asthma-like airway diseases or conditions the very short pulse of nitric oxide is timed to fall just before the end of the inhalation. This leaves the nitric oxide in contact with the airway smooth muscle in sufficient concentration to cause relaxation, but because at the end of the inhalation the airway is flushed of all the nitric oxide by the air coming from alveoli and lung periphery, so there is avoided prolonged exposure with the consequent risk of the formation of toxic nitrogen dioxide.

This previous invention concerns the administration of nitric oxide. The present invention stems from the appreciation that the same controlled breathing-related "pulsatile" delivery to the Patient's lungs can be usefully employed with many other medicaments; the invention is thus treatment apparatus - and in particular small (pocket-sized) hand-held apparatus - that utilises the "spike" principle. More specifically, the invention proposes apparatus for the delivery of a medicament - a drug, which can be in liquid or in solid (powder) form - into the Patient's lungs in the form of a bolus, pulse, or spike of the medicament entrained in and driven by the normal respiration air, which apparatus comprises in essence a drug dispenser (which might be a conventional liquid-dispensing nebuliser or a dry-powder dispenser, in the reservoir of which is stored the medicament to be administered,) driven by some suitable pressurised gas from a valved cylinder thereof to deliver an aerosol cloud of medicament into a tube through which the Patient is breathing (by mouth)

normal air, the gas cylinder valve being controlled by a suitably programmed computing device that is fed data describing the pressure within the breathing tube and so is able to open and close the valve at and for a time such as to drive the drug dispenser to deliver (to the tube and thence to the Patient's lungs) a required pulse of medicament at any selected point within the Patient's respiratory cycle.

In one aspect, therefore, the invention provides miniature, pocket-sized, hand-holdable apparatus for the delivery of a medicament into the Patient's lungs in the form of a bolus, pulse, or spike of the medicament entrained in and driven by the normal respiration air, which apparatus comprises:

- a tube through which the Patient is able to breath (by mouth) normal air;

- a drug dispenser (in the reservoir of which is storable the medicament to be administered) the output of which is deliverable into the tube for inhalation by the Patient;

- a valved cylinder for a suitable pressurised gas, which cylinder is connectable to the dispenser so as in use to drive the dispenser to deliver an aerosol cloud of medicament into the tube;

- pressure sensing means located within or operably connected to the tube, and able to provide data about the air pressure therewithin, and thus about the Patient's respiratory cycle; and

- programmed computing means operatively connectable to the gas cylinder valve so as to be able to open and shut that valve, and able to receive pressure data from the pressure sensing means;

such that the computing means can utilise the pressure data to enable the gas cylinder to drive the dispenser to deliver (to the tube and thence to the Patient's lungs) a required pulse of medicament at any selected point within the Patient's respiratory cycle.

The apparatus of this is intended to be portable. Indeed, it is the primary purpose of the invention to provide the apparatus in light, pocket-sized form small enough to be held in the hand, and to be used while being so held, and accordingly, hereinafter the apparatus is described in terms most appropriate for such a small hand-held piece of kit.

The invention provides apparatus for the delivery of a medicament into the Patient's lungs. The medicament can be any such material that might need to be administered to the lungs. For example, to treat asthma the medicament could be a bronchodilator such as SALBUTAMOL or TERBUTALINE or a steroid such as BECLOMETHASONE or FLIXOTIDE, while to treat an actual lung infection the medicament might be an antibiotic such as TICARCILLIN or COLISTIN.

The medicament may be formulated in any way that is both appropriate to the active ingredient of the medicament and to the need to have it turn into an aerosol spray in use. It may be presented as a solution or suspension in some liquid - water, perhaps - or it may even be supplied as a fine powder, possibly with or absorbed onto a powder carrier (when in a liquid form the drug is delivered to the Patient as an aerosol of fine droplets; when in solid/powder form it is delivered as a cloud of dust particles). By way of example, the asthma-treating medicament FLIXOTIDE is conveniently used in the form of dry powder, while the sputum lytic

agent rhDNase is advantageously delivered in the form of a liquid aerosol (droplets of liquid suspended in gas).

The invention's apparatus delivers its medicament into the lungs in the form of a bolus, pulse, or spike of the medicament entrained in and driven by the normal respiration air. The idea of this is simply to ensure that a high proportion of the medicament reaches and affects the target area and the target area only, rather than having the whole of the lungs subjected to it. The smaller the bolus - the shorter the pulse - the better this specificity is achieved. In some cases the pulse will be very short indeed, and while it is difficult to define precisely what is meant by "very" short, the following comments may be of assistance. The term "very short" means primarily that the provision of sufficient medicament for each bolus thereof is achieved by supplying the driving gas for a time period - of the order of a few tens of milliseconds - that is very short compared with the length of an average inhalation (which is about 1.5 second). However, there is more to the shortness of the pulse than just its temporal duration, for, the purpose of the pulse being to provide a bolus of medicament both of relatively high concentration and of relatively short physical length, both the actual flow rate of the medicament (perhaps in its carrier mixture form) as it is fed to the Patient and also the actual concentration of the medicament in that fed gas are important factors. What has been determined by experiment is that very satisfactory results are obtained using pulse durations of a few tens of milliseconds, and typically 20 to 30 msec. Thus, while it will clearly be understood that what is a "very short" pulse depends upon the flow rate and concentration of the administered medicament, nevertheless it can now be said that the term "very

short" means "of the order of a few units or tens of milliseconds". Or, to put it another way, the term means roughly one thousandth of the length of an average inhalation.

In the apparatus of the invention the medicament is driven into the Patient's lungs through a tube through which the Patient is breathing (by mouth) normal air. This tube is essentially nothing more than a short open-ended hollow cylinder - say, 5in (13cm) long and 1in (2.5cm) external diameter - possibly with a flattened mouthpiece to make it more convenient for the Patient to use, and nothing more need be said about it here.

The apparatus of the invention incorporates a drug dispenser in the reservoir of which is storable the medicament to be administered. It is the output of the dispenser which is deliverable into the tube for inhalation by the Patient.

One form of drug dispenser is the conventional nebuliser. Nebulisers - "cloud-formers" - are in general well-known items of equipment, commonly encountered in scent sprays, aerosol sprays, and carburettors, and little need be said about them here. Even so, it is convenient to note that a nebuliser is a basically a reservoir that has a fine orifice through which its contents may exit and across which is blown a stream of gas along a pipeway. As the gas flows past the orifice it causes an external pressure drop (relative to the reservoir's internal pressure: this pressure drop can be enhanced by shaping the pipeway as a Venturi constriction at the appropriate position), and so some of the reservoir's contents is "sucked" out into the gas stream and breaks up into an aerosol-like cloud of drops or particles that is then swept along the pipeway by the driving gas. It is convenient to include

within the pipeway downstream of the orifice an obstacle, or baffle, that is positioned within the path of the emerging drop/particle stream so as to impede all but the smallest drops/particles, which smallest ones are of a size most appropriate to being transported to the farthest reaches of the lung. For a small hand-held device the nebuliser is conveniently around 2.5in (6cm) long and an inch (2.5cm) or so across, the reservoir holding perhaps 1.5cu.in (25cc) of medicament formulation.

An alternative form of dispenser is the dry-powder dispenser, another well-established piece of equipment in which fine particles of medicament are held without liquid (indeed in some cases are created at the time of use by abrasion of a solid or compacted tablet) and are caused to enter the inspired airstream.

The drug dispenser (of whatever sort) employed in the invention's apparatus is driven by a suitable gas from a valved cylinder thereof, so as to produce the desired aerosol cloud of medicament and drive it into the tube. This gas can be simply a carrier - thus, an effectively inert (to the Patient) gas such as carbon dioxide or nitrogen - but it may be advantageous if the gas itself have some suitable medicinal action. For example, the gas might well be nitrous oxide (N_2O). There is little else to say about this, save that gas in the cylinder is likely to be at a high pressure, and so should be regulated to provide a lower, and constant, pressure appropriate to the operation of the dispenser, and save also that the gas cylinder (and any regulating means) should clearly be of a size and strength suitable to its intended purpose - and for a hand-held device an appropriate size is, much like the drug dispenser,

around 3in (7.5cm) long and an inch (2.5cm) or so across, and holding perhaps 2cu.in (35cc) of liquified gas under a pressure of 50bar (3MPa, or 700lbs/sq. in).

The cylinder is, of course, a valved cylinder, and the operation of the valve is controlled by the computing means (via some suitable actuating means) in response to the computing means' programming and input from the pressure sensor. The valve mechanism may take any appropriate form - it is typically an electromagnetically-actuated device such as one of those miniature solenoid valves available from Parker Hannifin Corp., Pneutronics Div., Hollis, New Hampshire, USA, and is conveniently powered from the computing means' power source.

The invention's apparatus includes pressure sensing means located within or connectable to the tube, and in use providing the computing means with data about the air pressure therewithin, and thus about the Patient's respiratory cycle. The sensor may be any suitable pressure-detecting transducer with an electrical output, and one preferred sensor is that available under the designation 24/26PC from Honeywell Inc., Freeport, Illinois, USA.

Controlling the whole operation of the medicament administering apparatus of the invention is the programmed computing means. This is operatively connectable to the gas cylinder valve (via its actuating means) so as to be able to open and shut that valve, it receives pressure data from the pressure sensing means so that it "knows" at all times the progress of the Patient's respiratory cycle, and it is programmed to make use of that information so as to enable the gas cylinder to drive the drug dispenser to deliver (to the tube and thence to the Patient's lungs) a required pulse

of medicament at any selected point within that cycle. Notionally, the computing means could be a general purpose microcomputer appropriately programmed and able to deal with the relevant inputs and outputs from and to the real world. In practice, though, the computing means is most advantageously a simple single chip computer "hard wired", or programmed in ROM, to take the relevant actions. Such a computer can be no more than 2in (5cm) or so long and wide, and 0.5in (1.25cm) deep, and can run off a small battery. It is ideally suited for use in a hand-held medicament-delivery system.

The programmed computing means takes the pressure data and in accordance with its program makes use of that information so as to enable the gas cylinder to drive the drug dispenser to deliver (to the tube and thence to the Patient's lungs) a required pulse of medicament at any selected point within that cycle. Which point that is, and for how long the pulse will last, is dependent upon the Patient's illness and the medicament being taken (this has been touched upon hereinbefore). The treatment of some conditions might require very short pulses to be delivered right at the beginning of the inspiration phase of the respiratory cycle - as the Patient draws in the next breath - while in contrast the treatment of others might require rather longer pulses to be delivered at the end of the inspiration phase of the respiratory cycle - as the Patient finishes inhaling the present breath and just before the exhale starts.

The primary purpose of the programmed computing means is to control the dispensing of the relevant medicament in dependence upon the respiratory data it receives, and in this connection the operation of the

dispenser may be improved if the computing means utilises an algorithm to optimize the detection of the breathing cycle in the presence of artefacts. In addition, however, the computing means can usefully gather data about the patient's respiration, and about apparatus usage and drug-dispenser changes, and then compute (and present) details of the patient's respiratory statistics, and so on. Moreover, it may be desirable to provide additional control of apparatus usage in accordance with data that may be pre-programmed into the apparatus or even encoded on (and read off) the drug container, or computed from the detected patient breathing cycle. Additionally, it may be desirable to enable the prevention of drug delivery in the absence of appropriate User/Patient identification by means of button/keyboard interaction. Accordingly, preferred embodiments of the medicament delivery apparatus of the invention include the following:-

A coding system (whether optical, electrical or by physical shape or other means) by which the contents of the drug container and the date limits of its contents may be detected by the programmed computing means and reported to the user, or employed in the control of the drug-dispensing process.

A visual or audible display system in which information may be provided to the User on the operation of the device, the status of the drug container or the parameters of their breathing process as measured by the pressure-sensing means and computed by the programmed computing means.

A means whereby the User may provide information to the programmed computing means, typically one or more electrical buttons or a miniature keypad.

An embodiment of the invention is now described, though by way of illustration only, with reference to the accompanying Drawings in which:

Figure 1 shows in cut-away perspective form apparatus of the invention for administering a medicament in controlled pulses to the Patient's lungs;

Figure 2 shows a bolus of medicament/air mixture travelling down deep into the Patient's lungs;

Figure 3 shows graphically the Patient's respiration, and the timing of the medicament pulses at the start of an inhalation; and

Figure 4 is a black box schematic of the overall drug dispenser/microcomputer system of the invention;

The apparatus shown in Figure 1 is in principle very simple. It comprises a drug dispenser in the form of a nebuliser (generally 11) having a reservoir (12) of medicament formulation (13) having an output tube (14) open as a "jet" (15) at the top (as viewed) to the "outside". The jet orifice is within a Venturi portion (16) of a deliver pipe (17) along which is fed pressurised gas from a storage cylinder (18) via a control valve (19). The valve is operated by actuating

means (100) itself driven by control signals from a single chip microcomputer (101: shown as a flat board).

The released gas and the "sucked out" medicament pass, via a baffle (102), into the apparatus' main breathing tube (103) by way of a second jet orifice (104), and there it mixes with the air that the Patient (not shown) draws in through a mouthpiece (105) at the tube's open end to provide lung-filling breaths.

A pressure-sensing transducer (106) is connected by a short pipe (107) opening into the tube 103 roughly intermediate the two ends. The transducer's output is fed to the microcomputer 101. The microcomputer uses this information to enable the gas cylinder valve 19 at predetermined times and for a predetermined duration in accordance with its programming (which is tailored to fit the Patient's disease or condition).

Figure 2 shows the progress of a bolus (21) of medicament/air mixture down the Patient's windpipe (22) and on deep into his lungs (23). Though at first sight it looks as though there are several bolus preceding one after the other, in fact there is only one, shown at different times on its journey, and the object of the Figure is to show how the bolus remains as an entity, and does not disperse as it progresses (and so reaches the deepest part of the lungs as a concentrated burst of medicament with the full therapeutic effect required).

The timing of the bolus delivery is shown graphically in Figure 3. Airflow in and out of the lungs takes place at regular intervals, as the Patient breathes, and just as the flow starts a pulse of medicament is delivered, and "washed down" with the remaining inhaled air.

The black box schematic of Figure 4 indicates the manner in which the microcomputer 101 operates in connection with the other parts. It needs no further comment at this time.

CLAIMS

1. Miniature, pocket-sized, hand-holdable apparatus for the delivery of a medicament into the Patient's lungs in the form of a bolus, pulse, or spike of the medicament entrained in and driven by the normal respiration air, which apparatus comprises:

a tube through which the Patient is able to breath (by mouth) normal air;

a drug dispenser (in the reservoir of which is storable the medicament to be administered) the output of which is deliverable into the tube for inhalation by the Patient;

a valved cylinder for a suitable pressurised gas, which cylinder is connectable to the dispenser so as in use to drive the dispenser to deliver an aerosol cloud of medicament into the tube;

pressure sensing means located within or operably connected to the tube, and able to provide data about the air pressure therewithin, and thus about the Patient's respiratory cycle; and

programmed computing means operatively connectable to the gas cylinder valve so as to be able to open and shut that valve, and able to receive pressure data from the pressure sensing means;

such that the computing means can utilise the pressure data to enable the gas cylinder to drive the dispenser to deliver (to the tube and thence to the Patient's lungs) a required pulse of medicament at any selected point within the Patient's respiratory cycle.

2. Apparatus as claimed in Claim 1, wherein the tube through which the Patient is to breath is a short open-ended hollow cylinder with a flattened mouthpiece.

3. Apparatus as claimed in either of the preceding Claims, wherein the drug dispenser is a nebuliser which comprises a reservoir that has a fine orifice through which its contents may exit and across which is blown a stream of gas along a pipeway, and included within the pipeway downstream of the orifice is an obstacle, or baffle, that is positioned within the path of the emerging drop/particle stream so as to impede all but the smallest drops/particles.
4. Apparatus as claimed in any of the preceding Claims, wherein the drug dispenser is driven by a suitable gas under pressure from a valved cylinder thereof, and there is a regulator to provide a lower, and constant, pressure appropriate to the operation of the dispenser.
5. Apparatus as claimed in any of the preceding Claims, wherein the valve of the gas cylinder, which valve is controlled by the computing means, is an electromagnetically-actuated miniature solenoid valve.
6. Apparatus as claimed in any of the preceding Claims, wherein the pressure sensing means is spaced from but connectable to the tube.
7. Apparatus as claimed in any of the preceding Claims, wherein the pressure sensing means is, or includes, a pressure-detecting transducer with an electrical output.
8. Apparatus as claimed in any of the preceding Claims, wherein the programmed computing means is a simple single chip computer "hard wired", or programmed in ROM, to take the relevant actions.
9. Apparatus as claimed in any of the preceding Claims and substantially as described hereinbefore.




Fig. 1




Fig. 2




Fig. 3




Fig. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/01994

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61M11/06 A61M15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 404 871 A (GOODMAN DAVID E ET AL) 11 April 1995 see claims 1,6,8 ---	1-9
Y	US 5 318 015 A (MAANSSON SVEN ET AL) 7 June 1994 see column 3, line 1 - line 63; figure 1 ---	1-9
A	US 3 069 097 A (CHENEY) 18 December 1962 see claim 8; figures 1-5 ---	1-4
A	WO 86 01731 A (VORTTRAN CORP) 27 March 1986 see claims 1-8; figures ---	1-4
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

5 March 1999

Date of mailing of the international search report

12/03/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Villeneuve, J-M

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 98/01994

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 48431 A (AID MEDIC LTD ;DENYER JONATHAN STANLEY HAROLD (GB); DYCHE ANTHONY) 24 December 1997 see abstract see page 13, line 34 - page 14, line 2 ---	1,6
A	DE 40 09 067 A (SAUSEN THOMAS) 5 December 1991 see claims 1-3 ---	1
E	GB 2 320 900 A (UNIV SHEFFIELD) 8 July 1998 see the whole document -----	1-9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/01994

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5404871 A	11-04-1995	CA 2082168 C EP 0529053 A JP 9164205 A JP 2613347 B US 5394866 A US 5469750 A US 5450336 A US 5392768 A WO 9215353 A US 5522378 A US 5542410 A US 5622162 A US 5497764 A US 5520166 A US 5608647 A US 5655516 A US 5743252 A US 5755218 A US 5813397 A US 5826570 A	26-03-1996 03-03-1993 24-06-1997 28-05-1997 07-03-1995 28-11-1995 12-09-1995 28-02-1995 17-09-1992 04-06-1996 06-08-1996 22-04-1997 12-03-1996 28-05-1996 04-03-1997 12-08-1997 28-04-1998 26-05-1998 29-09-1998 27-10-1998
US 5318015 A	07-06-1994	AU 4989993 A WO 9405357 A	29-03-1994 17-03-1994
US 3069097 A	18-12-1962	NONE	
WO 8601731 A	27-03-1986	EP 0194258 A	17-09-1986
WO 9748431 A	24-12-1997	GB 2316323 A AU 3184597 A DE 29723053 U	25-02-1998 07-01-1998 16-04-1998
DE 4009067 A	05-12-1991	DE 9003317 U	31-10-1990
GB 2320900 A	08-07-1998	NONE	